



UNIVERSAL WOODGRAIN SERIES DOOR SPECIFICATIONS

Universal WoodGrain Series: High quality, 25 gauge 2' thick non-insulated steel door

Specifications:

Sections: Are 2 inches thick in 21 and 18 inch section heights. Each section is manufactured from 25 gauge hot dipped galvanized steel. Sections are pre painted white and rotary embossed with a wood grain texture. Traditional definition raised panels are pressed in 1/8" height increments to a depth of .375". Tongue and groove metering rails are roll formed into the panel incorporating the "RITS" reinforced integral truss system. Vertical stile members are 19 gauge hot dipped galvanized I beams for center and end stiles are formed to encapsulate the pan. Stiles are riveted and bonded to the interior face of the door with epoxy based cement. Bottom sections are reinforced with aluminum "L" angle, and bonded to the bottom of the section for supporting a replaceable UV protected bottom weather seal.

H 2 Hardware And Track: Hinges are hot dipped galvanized, 14/16 gauge wide body end roller hinges and 14/16 gauge interior hinges. Rollers are 2 inch black nylon or optional white nylon; galvanized torsion tube; self locking fasteners, pre painted torsion springs, and an optional inside slide lock.

Models:

Short Panel 25 gauge door embossment is Traditional Definition
Long Panel 25 gauge door embossment is Traditional Definition
Bead Board 25 gauge door embossment is Traditional Definition
Flush Panel 25 gauge door embossment is no definition

Widths & Heights: Widths: 8', 9', 10', 12', 14', 15', 15'8", 16', 18'
Heights: 6'0" thru 14'0" (3" increments). Additional heights available

Up Grade Options:

Glass Designs: Various Designs - See Brochure
Decorative Hardware: Various Designs - See Brochure

Insulation: CFC free polystyrene insulation with a rigid high impact vinyl back skin with an R factor of 6.25. CFC free polystyrene insulation.

Hardware: H 1 Optional hardware includes 16 gauge commercial hinges throughout. JR. Residential A top fixtures and RBB bottom fixtures, 10 ball black Poly rollers, lift handles, Pre painted spring, galvanized torsion tube, .045 vertical track, and .055 horizontal track.